

.....
FOR HEAT PUMP SYSTEMS
.....

BUFFER TYPE TANKS

40–500L



NEW TANKS SERIES BAC-0 & BLS-0

SPECIALLY DESIGNED FOR HEAT-COLD PUMPS



The new tanks BAC-0 & BLS-0 are Buffer type tanks and available in capacities from 40 to 500L. They are offered with internal ENAMEL protection for storage of Domestic Hot Water (DHW), but also without enameling to use as a Buffer Tank CC (closed circuit) for integration to the central heating system.

They are designed for heat-cold pump systems, with the option to be installed horizontally or vertically.



BAC-0 40L (non enameled)

BLS-0 40L (enameled)





| | | |
|-------------------------------|-----|--|
| Capacity | L | 41 |
| Maximum operating temperature | °C | 95 |
| Tank material | | Hot or cold rolled metal sheet 2mm (EN 10025, EN 10130) |
| Outer shell material | | Pre-Painted (Ral 9006) galvanized metal sheet 0.5mm (EN 10204) |
| Insulation | | Polyurethane Foam 48kg / m ³ (DIN 53420), self-extinguishing (DIN 4102) |
| Maximum pressure | bar | 6 |
| Outer diameter | mm | Ø400 |
| Inner diameter | mm | Ø300 |
| a | mm | 137.5 |
| b | mm | 222.5 |
| c | mm | 222.5 |
| d | mm | 137.5 |
| e | mm | 720 |
| L1, L3, L4 & L5 | | G 1¼" |
| L2 | | G ½" |
| AV (air vent) | | G 1" |
| D (drain) * | | G 1" |

* Suitable to install heating element.
Specification and design are subject to change without any notice.

BAC-0 60L (non enameled)

BLS-0 60L (enameled)





| | | |
|-------------------------------|-----|--|
| Capacity | L | 52 |
| Maximum operating temperature | °C | 95 |
| Tank material | | Hot or cold rolled metal sheet 2mm (EN 10025, EN 10130) |
| Outer shell material | | Pre-Painted (Ral 9006) galvanized metal sheet 0.5mm (EN10204) |
| Insulation | | Polyurethane foam 48kg / m ³ (DIN 53420), self-extinguishing (DIN 4102) |
| Maximum pressure | bar | 6 |
| Outer diameter | mm | Ø400 |
| Inner diameter | mm | Ø300 |
| a | mm | 152.5 |
| b | mm | 190 |
| e | mm | 875 |
| L1,L2, L3, L4,L5,L6,L7 & L8 | mm | G 1¼" |
| AV (air vent) | mm | G 3/4" |
| D (drain) * | | G 1½" |

* Suitable to install heating element.
Specification and design are subject to change without any notice.

BAC-0 80L (non enameled)

BLS-0 80L (enameled)





| | | |
|-------------------------------|-----|--|
| Capacity | L | 80 |
| Maximum operating temperature | °C | 95 |
| Tank material | | Hot or cold rolled metal sheet 2mm (EN 10025, EN 10130) |
| Outer shell material | | Pre-Painted (Ral 9006) galvanized metal sheet 0.5mm (EN10204) |
| Insulation | | Polyurethane Foam 48kg / m ³ (DIN 53420), self-extinguishing (DIN 4102) |
| Maximum pressure | bar | 6 |
| Outer diameter | mm | Ø460 |
| Inner diameter | mm | Ø360 |
| a | mm | 172,5 |
| b | mm | 190 |
| e | mm | 910 |
| L1,L2, L3, L4,L5,L6,L7 & L8 | mm | G 1¼" |
| AV (air vent) | mm | G 3/4" |
| D (drain) * | | G 1½" |

* Suitable to install heating element.
Specification and design are subject to change without any notice.

BAC-0 100L (non enameled)

BLS-0 100L (enameled)





| | | |
|-------------------------------|-----|--|
| Capacity | L | 92.5 |
| Maximum operating temperature | °C | 95 |
| Tank material | | Hot or cold rolled metal sheet 2,5mm (EN 10025, EN 10130) |
| Outer shell material | | Pre-Painted (Ral 9006) galvanized metal sheet 0.5mm (EN10204) |
| Insulation | | Polyurethane Foam 48kg / m ³ (DIN 53420), self-extinguishing (DIN 4102) |
| Maximum pressure | bar | 8 |
| Outer diameter | mm | Ø500 |
| Inner diameter | mm | Ø400 |
| a | mm | 192.5 |
| b | mm | 190.0 |
| c | mm | 192.5 |
| e | mm | 960 |
| L1, L3, L4,L5, L6, L7& L8 | | G 1¼" |
| AV (air vent) | | G 3/4" |
| D (drain) * | | G 1 1/2" |

* Suitable to install heating element.
Specification and design are subject to change without any notice.

BAC-0 150L (non enameled)

BLS-0 150L (enameled)




| | | |
|-------------------------------|-----|--|
| Capacity | L | 144 |
| Maximum operating temperature | °C | 95 |
| Tank material | | Hot or cold rolled metal sheet 2,5mm (EN 10025, EN 10130) |
| Outer shell material | | Pre-Painted (Ral 9006) galvanized metal sheet 0.5mm (EN10204) or PVC |
| Insulation | | Polyurethane Foam 48kg / m ³ (DIN 53420), self-extinguishing (DIN 4102) |
| Maximum pressure | bar | 8 |
| Outer diameter | mm | Ø560 |
| Inner diameter | mm | Ø450 |
| a | mm | 235 |
| b | mm | 595 |
| c | mm | 835 |
| d | mm | 435 |
| e | mm | 535 |
| f | mm | 635 |
| g | mm | 735 |
| h | mm | 835 |
| i | mm | 1120 |
| L1,L2,L3, L4,L5,L6& L7 | | G 1 1/2" |
| L8,L9&L10 | | G 1/2" |
| AV (air vent) | | G 1 1/2" |
| D (drain) | | G 1 1/2" |

Specification and design are subject to change without any notice.

BAC-0 200L (non enameled)

BLS-0 200L (enameled)





| | | |
|-------------------------------|-----|--|
| Capacity | L | 204 |
| Maximum operating temperature | °C | 95 |
| Tank material | | Hot or cold rolled metal sheet 2,5mm (EN 10025, EN 10130) |
| Outer shell material | | Pre-Painted (Ral 9006) galvanized metal sheet 0.5mm (EN10204) or PVC |
| Insulation | | Polyurethane Foam 48kg / m ³ (DIN 53420), self-extinguishing (DIN 4102) |
| Maximum pressure | bar | 8 |
| Outer diameter | mm | Ø590 |
| Inner diameter | mm | Ø480 |
| a | mm | 222 |
| b | mm | 722 |
| c | mm | 1112 |
| d | mm | 597 |
| e | mm | 757 |
| f | mm | 907 |
| g | mm | 1062 |
| h | mm | 1112 |
| i | mm | 1400 |
| L1,L2,L3, L4,L5,L6& L7 | | G 1 1/2" |
| L8,L9&L10 | | G 1/2" |
| AV (air vent) | | G 1 1/2" |
| D (drain) | | G 1 1/2" |

Specification and design are subject to change without any notice.

BAC-0 300L (non enameled)

BLS-0 300L (enameled)





| | | |
|-------------------------------|-----|--|
| Capacity | L | 298 |
| Maximum operating temperature | °C | 95 |
| Tank material | | Hot or cold rolled metal sheet 2,5mm (EN 10025, EN 10130) |
| Outer shell material | | Pre-Painted (Ral 9006) galvanized metal sheet 0.5mm (EN10204) or PVC |
| Insulation | | Polyurethane Foam 48kg / m ³ (DIN 53420), self-extinguishing (DIN 4102) |
| Maximum pressure | bar | 8 |
| Outer diameter | mm | Ø630 |
| Inner diameter | mm | Ø520 |
| a | mm | 233 |
| b | mm | 933 |
| c | mm | 1323 |
| d | mm | 808 |
| e | mm | 968 |
| f | mm | 1118 |
| g | mm | 1273 |
| h | mm | 1323 |
| i | mm | 1630 |
| L1,L2,L3, L4,L5,L6& L7 | | G 2" |
| L8,L9&L10 | | G ½" |
| AV (air vent) | | G 1 1/2" |
| D (drain) | | G 1 1/2" |

Specification and design are subject to change without any notice.

BAC-0 500L (non enameled)

BLS-0 500L (enameled)



| | | |
|-------------------------------|-----|--|
| Capacity | L | 478 |
| Maximum operating temperature | °C | 95 |
| Tank material | | Hot or cold rolled metal sheet 3,0mm (EN 10025, EN 10130) |
| Outer shell material | | Pre-Painted (Ral 9006) galvanized metal sheet 0.5mm (EN10204) or PVC |
| Insulation | | Polyurethane Foam 48kg / m ³ (DIN 53420), self-extinguishing (DIN 4102) |
| Maximum pressure | bar | 8 |
| Outer diameter | mm | Ø750 |
| Inner diameter | mm | Ø640 |
| a | mm | 251 |
| b | mm | 951 |
| c | mm | 1341 |
| d | mm | 826 |
| e | mm | 986 |
| f | mm | 1136 |
| g | mm | 1291 |
| h | mm | 1341 |
| i | mm | 1679 |
| L1,L2,L3, L4,L5,L6& L7 | | G 3" |
| L8,L9&L10 | | G ½" |
| AV (air vent) | | G 1 1/2" |
| D (drain) | | G 1 1/2" |

Specification and design are subject to change without any notice.



